

ENGINE DETAILS

Delivers consistent, easy starting, crisp throttle response, increased fuel economy, and outstanding overall performance. Great for aluminum tiller, aluminum console, jon, utility, and fish & ski boats.

SPECIFICATIONS - 25 EFI

HP / kW	25 / 18.6
Engine type	Inline 3
Displacement (CID/CC)	32.1 / 526
Full throttle RPM	5000-6000
Fuel induction system	2 valves per cylinder, single overhead cam (SOHC)
Alternator amp / Watt	15 amp / 186 watt
Recommended fuel	87 octane / up to 10% ethanol
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	Low oil pressure Over-rev Overheat Sensor failure
Starting	Electric (turn-key) Manual
Steering	Remote Tiller
Shaft length	15" / 381 mm 20" / 508 mm
Gearcase ratio	1.92:1
Dry weight *Lightest model available	157 lbs / 71 kg



Lakeway Marine
Lot 4 Parkside Drive (Hwy. 59-44)
Lockport, Manitoba
Phone: (204) 757-9440
www.Lakewaymarine.ca

CARB star rating	3
Bore and stroke	2.40 x 2.36" / 61 x 60 mm
Ignition	CDI w/electronic spark advance
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard
Trim system	Manual Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	16
Remote fuel tank standard (gal / L)	6.6 / 25
Color	Phantom Black