

ENGINE DETAILS

Feature integral fuel tanks with an external fuel-shutoff valve. For extended range, they can also be connected to a remote fuel tank. Great for aluminum tiller, inflatable soft hull, jon, utility, and sail boats.

SPECIFICATIONS - 6

HP / kW	6 / 4.4
Engine type	1 cylinder
Displacement (CID/CC)	7.5 / 123
Full throttle RPM	5000-6000
Fuel induction system	2-valve pushrod (overhead valve)
Recommended fuel	87 octane / up to 10% ethanol
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	Low oil pressure Over-rev
Starting	Manual
Steering	Tiller
Shaft length	15" / 381 mm 20" / 508 mm
Gearcase ratio	2.15:1
Dry weight *Lightest model available	57 lbs / 26 kg
CARB star rating	3
Bore and stroke	2.32 x 1.77" / 59 x 45 mm
Ignition	CDI w/electronic spark advance
Fuel system	Carbureted
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard
Trim positions	6



Lakeway Marine
Lot 4 Parkside Drive (Hwy. 59-44)
Lockport, Manitoba
Phone: (204) 757-9440
www.Lakewaymarine.ca

Exhaust system	Through prop
Shallow water drive	Yes
Shallow water trim range (degrees)	16
Integrated fuel tank (gal / L)	0.3 / 1.1
Optional fuel tank (gal / L)	3.2 / 12
Color	Phantom Black