

## ENGINE DETAILS

Built to deliver the type of power, thrust, and control that wider, heavier boats require. Great for aluminum tiller, inflatable soft hull, jon, utility, and sail boats.

### 2018 - Mercury 9.9 MLH 4S L/S

HP / kW	<b>9.9 / 7.3</b>
Engine type	<b>Inline 2</b>
Displacement (CID/CC)	<b>12.8 / 208</b>
Full throttle RPM	<b>5000-6000</b>
Fuel induction system	<b>2 valves per cylinder, single overhead cam (SOHC)</b>
Alternator amp / Watt	<b>6 amp / 76 watt</b>
Recommended fuel	<b>87 octane / up to 10% ethanol</b>
Recommended oil	<b>Mercury FourStroke Oil 10W-30</b>
Engine protection operator warning system	<b>Low oil pressure Over-rev</b>
Starting	<b>Electric Manual</b>
Steering	<b>Remote Tiller</b>
Shaft length	<b>15" / 381 mm 20" / 508 mm 25" / 635 mm (CT model)</b>
Gearcase ratio	<b>2.08:1 or 2.42:1 (CT model)</b>
Dry weight *Lightest model available	<b>84 lbs / 38 kg</b>
CARB star rating	<b>3</b>
Bore and stroke	<b>2.16 x 1.73" / 55 x 44 mm</b>
Ignition	<b>CDI w/electronic spark advance</b>
Fuel system	<b>Carbureted</b>
Cooling system	<b>Water-cooled with thermostat</b>
Gear shift	<b>F-N-R</b>



**Lakeway Marine**  
Lot 4 Parkside Drive (Hwy. 59-44)  
Lockport, Manitoba  
Phone: (204) 757-9440  
[www.Lakewaymarine.ca](http://www.Lakewaymarine.ca)

Gearcase options	<b>Command Thrust (CT) Standard</b>
Trim system	<b>Power Tilt (CT model)</b>
Trim positions	<b>Ratcheting</b>
Exhaust system	<b>Through prop</b>
Shallow water drive	<b>Yes</b>
Shallow water trim range (degrees)	<b>16</b>
Remote fuel tank standard (gal / L)	<b>3.2 / 12</b>
Color	<b>Phantom Black</b>