

ENGINE DETAILS

Built to deliver the type of power, thrust, and control that wider, heavier boats require. Great for aluminum tiller, inflatable soft hull, jon, utility, and sail boats.

2021 - Mercury 9.9 MH 4S S/S

HP / kW	9.9 / 7.3
Engine type	Inline 2
Displacement (CID/CC)	12.8 / 208
Full throttle RPM	5000-6000
Fuel induction system	2 valves per cylinder, single overhead cam (SOHC)
Alternator amp / Watt	6 amp / 76 watt
Recommended fuel	87 octane / up to 10% ethanol
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	Low oil pressure Over-rev
Starting	Electric Manual
Steering	Remote Tiller
Shaft length	15" / 381 mm 20" / 508 mm 25" / 635 mm (CT model)
Gearcase ratio	2.08:1 or 2.42:1 (CT model)
Dry weight *Lightest model available	84 lbs / 38 kg
CARB star rating	3
Bore and stroke	2.16 x 1.73" / 55 x 44 mm
Ignition	CDI w/electronic spark advance
Fuel system	Carbureted
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R



Lakeway Marine
Lot 4 Parkside Drive (Hwy. 59-44)
Lockport, Manitoba
Phone: (204) 757-9440
www.Lakewaymarine.ca

Gearcase options	Command Thrust (CT) Standard
Trim system	Power Tilt (CT model)
Trim positions	Ratcheting
Exhaust system	Through prop
Shallow water drive	Yes
Shallow water trim range (degrees)	16
Remote fuel tank standard (gal / L)	3.2 / 12
Color	Phantom Black