



Lakeway Marine Inc.

Lot 4 Parkside Drive (Hwy 44 & 59)

Lockport, MB PH: (204) 757-9440

Email: lakewaymarine@highspeedcrow.ca

Web Site: www.Lakewaymarine.ca

ENGINE INFORMATION AND SPECIFICATIONS

ENGINE DETAILS

Get massive displacement and power from the lightest, easiest-to-maintain 150hp FourStroke on the market. Great for bass, aluminum console, runabout open bow, and offshore fishing boats and pontoons.

SPECIFICATIONS - 150

HP / kW	150 / 110
Engine type	8-valve single overhead cam (SOHC) Inline 4
Displacement (L)	3.0
Full throttle RPM	5000-5800
Air induction	Performance-Tuned Scroll Intake Manifold
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	60 amp / 756 watt (Belt-Driven)
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Electric (turn-key) Smart Start Electric
Controls	Mechanical throttle & shift
Steering	Big Tiller Compatible Dual cable mechanical Electro-Hydraulic Power Steering Optional on Duals Hydraulic power steering
Shaft length	20" / 508 mm 25" / 635 mm
Gearcase ratio	1.92:1
Dry weight *Lightest model available	455 lbs / 206 kg

**Lakeway Marine Inc.**

Lot 4 Parkside Drive (Hwy 44 & 59)

Lockport, MB PH: (204) 757-9440

Email: lakewaymarine@highspeedcrow.caWeb Site: www.Lakewaymarine.ca

CARB star rating	3
Bore and stroke	4.0 x 3.6" / 102 x 92 mm
Ignition	SmartCraft ECM 70 Digital Inductive
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard
Trim system	Power Tilt Power Trim
Exhaust system	Through prop
Counter Rotation	Available
Color	Phantom Black
Lubrication system	Wet sump
Oil Capacity	6.3 qts / 6.0l
Maximum Trim Range	22° (-6° to 16°)
Maximum Tilt Range	73° (-6° to 67°)