

ENGINE INFORMATION AND SPECIFICATIONS

ENGINE DETAILS

Weighing in at just 38 pounds, this compact, reliable motor is a great choice for aluminum tiller, inflatable soft hull, jon, utility, and sail boats.

SPECIFICATIONS - 2.5

HP / kW	2.5 / 1.9
Engine type	1 cylinder
Displacement (CID/CC)	5.2 / 85
Full throttle RPM	4500-5500
Fuel induction system	2-valve pushrod (overhead valve)
Recommended fuel	87 octane compatible (up to 10% ethanol)
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	Over-rev
Starting	Manual
Steering	Tiller with 360° turning
Shaft length	15" / 381 mm
Gearcase ratio	2.15:1
Dry weight *Lightest model available	41 lbs / 18 kg

CARB star rating	3
Bore and stroke	2.16 x 1.42" / 55 x 36 mm
Ignition	CDI w/electronic spark advance
Fuel system	Carbureted
Cooling system	Water-cooled with thermostat
Gear shift	F-N
Gearcase options	Standard
Trim system	4 position
Trim positions	4
Exhaust system	Above prop
Shallow water trim range (degrees)	16
Integrated fuel tank (gal / L)	0.3 / 1.1
Color	Phantom Black