Lakeway Marine Inc.

Lot 4 Parkside Drive (Hwy 44 & 59) Lockport, MB PH: (204) 757-9440

Email: lakewaymarine@highspeedcrow.ca



Web Site: www.Lakewaymarine.ca



ENGINE INFORMATION AND SPECIFICATIONS

ENGINE DETAILS

Matches the acceleration and fuel efficiency of our competitor's more expensive 70hp outboard model. Great for aluminum tiller, aluminum console, jon, utility, and fish & ski boats.

SPECIFICATIONS - 60 EFI

HP / kW	60 / 45
Engine type	Inline 4
Displacement (CID/CC)	60.8 / 995
Full throttle RPM	5500-6000
Fuel induction system	2 valves per cylinder, single overhead cam (SOHC)
Alternator amp / Watt	18 amp / 226 watt
Recommended fuel	87 octane / up to 10% ethanol
Recommended oil	Mercury FourStroke 25W40 Marine Oil
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Electric (turn-key)
Steering	Remote Tiller
Shaft length	20" / 508 mm 25" / 635 mm (CT model)
Gearcase ratio	1.83:1 or 2.33:1 (CT model)
Dry weight *Lightest model available	247 lbs / 112 kg



Lakeway Marine Inc.

Lot 4 Parkside Drive (Hwy 44 & 59) Lockport, MB PH: (204) 757-9440

Email: lakewaymarine@highspeedcrow.ca

Web Site: www.Lakewaymarine.ca

CARB star rating	3
Bore and stroke	2.56 x 2.95" / 65 x 75 mm
Ignition	ECM 07 Digital Inductive (CT model) ECM 70
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Command Thrust (CT) Standard
Trim system	Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	20
Remote fuel tank (optional)	Yes
Color	Phantom Black
Lubrication system	Wet sump