

ENGINE INFORMATION AND SPECIFICATIONS

ENGINE DETAILS

Built to deliver the type of power, thrust, and control that wider, heavier boats require. Great for aluminum tiller, inflatable soft hull, jon, utility, and sail boats.

SPECIFICATIONS - 9.9

HP / kW **9.9 / 7.3**

Engine type **Inline 2**

Displacement (CID/CC) **12.8 / 208**

Full throttle RPM **5000-6000**

Fuel induction system **2 valves per cylinder, single overhead cam (SOHC)**

Alternator amp / Watt **6 amp / 76 watt**

Recommended fuel **87 octane / up to 10% ethanol**

Recommended oil **Mercury FourStroke Oil 10W-30**

Engine protection operator warning system **Low oil pressure
Over-rev**

Starting **Electric
Manual**

Steering **Remote
Tiller**

Shaft length **15" / 381 mm
20" / 508 mm
25" / 635 mm (CT model)**

Gearcase ratio **2.08:1 or 2.42:1 (CT model)**

Dry weight *Lightest model available **84 lbs / 38 kg**

**Lakeway Marine Inc.**

Lot 4 Parkside Drive (Hwy 44 & 59)

Lockport, MB PH: (204) 757-9440

Email: lakewaymarine@highspeedcrow.caWeb Site: www.Lakewaymarine.ca

CARB star rating	3
Bore and stroke	2.16 x 1.73" / 55 x 44 mm
Ignition	CDI w/electronic spark advance
Fuel system	Carbureted
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Command Thrust (CT) Standard
Trim system	Power Tilt (CT model)
Trim positions	Ratcheting
Exhaust system	Through prop
Shallow water drive	Yes
Shallow water trim range (degrees)	16
Remote fuel tank standard (gal / L)	3.2 / 12
Color	Phantom Black